

Ref. No.: 607-02121319





Description:

Used EISENMANN Dip coating line

In 2008, extensively modernized (expense approximately € 800 thousand)

- Completely new Siemens S7 PLC
- Furthermore, the evaporation zones were heated after the base or cover paint tank through a warm air blower.
- Also, the top coat dryer that existed prior to the renovation of three interconnected chambers with a common burner was changed. Currently, there are 3 separate chambers with separate temperature control available. The hanger through these 3 chambers in succession, the temperatures of the first to be increased to the third chamber until the baking temperature of the coating system is reached (temperature ramp)
- Goods and goods carrier single exit system (make: HERO) additionally installed => Goods carrier's facility must not leave, climb and hang Directly on goods carrier in the circulation system
- Cpl. System enclosure and implementation of a pressure system to avoid contamination in the system
- Forced air furnace changed (direction outlets, speeds, control options, ...)

u.v.m.

- Compl. Plant stands in its own steel construction, thus hall independent and can therefore complete. dismantled and reassembled be anywhere again
- Except for a 6 x 3 m wide range installation at ground level
- Currently designed for waterborne paint-2-layer systems (no ex-guards)
- Max. Possible submersible solids (L x W x H): 2.20 x 1.8 x 2.00 m
- Paint tank volume (L x W x H): 2.5 x 1.9 x 2.2m
- The treatment consists of four diving pool, two treatments and two sinks, respectively
 after degreasing and after iron phosphating both sink will go through in order to
 achieve a good rinse the parts and thus a clean process. The monitoring of the four
 methods baths carried conductivity-controlled largely automatically.
- Excerpts list of installed brand:
- Conveyor systems internally Eisenmann, enhanced by laser measuring systems and incremental encoders
- Placement machine iron man 2 pieces each with 500kg lifting capacity
- Paint pumps with barrier fluid: Grundfos

Generated on 17.10.2025 Page 2



- Frequency: Danfos
- dosing missing
- Direct heating burner:
 - 1x Cw-- GZ 180 E (Messrs. Junkers)
 - o 2x WG20N \ 1-CZ-LN (Fa.Weishaupt) 35 200KW
- Film speed doors 2 pcs: Albany Rapid Roll Type 392
- Exhaust and cooling system GEA
- All other pumps: KSB
- Conveyor system with lifting device before it is invested with crossways: HARO
- Temperature controls 12 pcs: JUMO dTRON (Compact Controller with program function)
- All stations with higher energy demand are equipped with lid / closure systems to reduce energy use in article support non-occupancy
 - paint tank
 - Flash-off / Abblasstationen
- Incl. Demineralization (reverse osmosis) for the production of demineralized water (Make: Model: RO 250 LE ST.
- Incl. Wastewater treatment plant; Saggars 3 m³; Storage tank 10m³
- Processes in the diving system are logged largely automated. In particular, the
 monitoring of the pretreatment and the paint tank is documented by the controller.
 This simplifies accountability in the event of mistakes in the painting results. All
 measurements and dosing are recognized by the controller and written at appropriate
 intervals to a log file.

For more info, photos and videos as well as dates for the inspections upon request.



Technical Data:

Technical Data:

Control: CNC

Buyer Information:

Condition: Very good condition

Available: Immediately

Sold as:

EXW (Ex Works - Incoterm)

VAT: 19 %

Buyers Premium: 15 % Location: Germany



Images:







































Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33