



Ref. No.:

1343-25101300

Overview and Technical Data:

SOKRATHERM GG 140 S - combined heat & power plant 142kW

SOKRATHERM



Year of Build:
Blockheizkraftwerke
Oct 2011

Description:

Used SOKRATHERM GG 140 SoE - Gas Combined heat & power unit 142kW

The natural gas-fueled cogeneration unit has a thermal output of 216 kW and an electrical output of 142 kW for the power supply, and is ideally suited to compensate for the constantly rising energy prices through self-generation. The CHP unit works on the principle of cogeneration, which means that in addition to electricity, heat can also be generated.

Stand 17.12.2021

- 60502 Bh
- 3768 Starts

Technical data

- Gross active power: 199 kW
- Net active power: 142 kW
- Apparent power: 177,5 kVA
- Rated voltage: 400 V
- Rated current: 257 A
- Electrical efficiency: 36,2
- Thermal power: 216 kW
- Thermal efficiency: 55,1
- Total efficiency: 91, 3%
- Gas consumption: 392 kW H
- Electric power factor: 0,64
- Primary energy factor: 0,194

- Maintenance interval: 1.500 operating hours
- Major overhaul: 50,000 after approx. [Bh]
- Airborne sound pressure level: 69 dB

Generator:

- Manufacturer: MarelliGenerators
- Model: MJB 250 LB4

CHP - combined heat and power plants

Combined heat and power plants or industrial plants that produce thermal energy and cogeneration, using a combustion engine to produce both electricity and heat. Especially in times when productivity and economic security are becoming increasingly important, CHP can contribute to environmental protection and at the same time reduce personnel costs. The operation of cogeneration is very efficient, as the combination of electricity generation and heat production can be up to 95% efficient. This is possible by using the heat generated during electricity production for heating purposes, which means that practically nothing is lost in terms of heat and energy. CHP is not only environmentally friendly, but can also reduce electricity bills, as self-produced electricity is often cheaper than the alternative grid.

Technical Data:

Technical Data:

Control:

CNC

Machine Hours:

3768

Dimensions and Weight:

Height:

1.830 mm

Length:

2.500 mm

Width:

900 mm

Weight:

2.850 kg

Buyer Information:

Condition:

Very good condition

Available:

Immediately

Sold as:

EXW (Ex Works - Incoterm)

VAT:

19 %

Buyers Premium:

16 %

Location:

Germany

Images:











SOKRATHERM® BHKW-Komplettmodul
BHKW-Compact CHP unit

BHKW-Typ CHP-type	GG 140 S 0 E	Spezifikation specification	WP 7L-70 B	Baujahr year of construction	2011
elektrische Nennleistung rated electric power	142 kW	thermische Nennleistung rated thermal power	216 kW	Energieeinsatz energy input	392 kW
Fertigungsnummer serial number	F110102	Aufstellhöhe altitude	<100 m üNN	max. Lufttemperatur max. air temperature	25 °C
Nendrehzahl rated speed	1500 1/min	Steuerspannung control voltage	24 V	Nennleistungsfaktor rated power factor	$\cos \varphi$ 0,8
Nennspannung rated voltage	400 V	max. Heizwasseraustritt max. heating water outlet			

Video:

Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

W-Kompaktmodul Email: info@asset-trade.de Moderne Energie- und Wärmetechnik

Web.: <https://mail.asset-trade.de/en>

Ref. No.:
1343-25101300

Overview and Technical Data:

SOKRATHERM GG 140 S - combined heat & power plant 142kW

SOKRATHERM



Year of Build:
Blockheizkraftwerke
Oct 2011

Description:

Used SOKRATHERM GG 140 SoE - Gas Combined heat & power unit 142kW

The natural gas-fueled cogeneration unit has a thermal output of 216 kW and an electrical output of 142 kW for the power supply, and is ideally suited to compensate for the constantly rising energy prices through self-generation. The CHP unit works on the principle of cogeneration, which means that in addition to electricity, heat can also be generated.

Stand 17.12.2021

- 60502 Bh
- 3768 Starts

Technical data

- Gross active power: 199 kW

- Net active power: 142 kW
- Apparent power: 177,5 kVA
- Rated voltage: 400 V
- Rated current: 257 A
- Electrical efficiency: 36,2
- Thermal power: 216 kW
- Thermal efficiency: 55,1
- Total efficiency: 91, 3%
- Gas consumption: 392 kW H
- Electric power factor: 0,64
- Primary energy factor: 0,194
- Maintenance interval: 1.500 operating hours
- Major overhaul: 50,000 after approx. [Bh]
- Airborne sound pressure level: 69 dB

Generator:

- Manufacturer: MarelliGenerators
- Model: MJB 250 LB4

CHP - combined heat and power plants

Combined heat and power plants or industrial plants that produce thermal energy and cogeneration, using a combustion engine to produce both electricity and heat. Especially in times when productivity and economic security are becoming increasingly important, CHP can contribute to environmental protection and at the same time reduce personnel costs. The operation of cogeneration is very efficient, as the combination of electricity generation and heat production can be up to 95% efficient. This is possible by using the heat generated during electricity production for heating purposes, which means that practically nothing is lost in terms of heat and energy. CHP is not only environmentally friendly, but can also reduce electricity bills, as self-produced electricity is often cheaper than the alternative grid.

Technical Data:

Technical Data:

Control:

CNC

Machine Hours:

3768

Dimensions and Weight:

Height:

1.830 mm

Length:

2.500 mm

Width:

900 mm

Weight:

2.850 kg

Buyer Information:

Condition:

Very good condition

Available:

Immediately

Sold as:

EXW (Ex Works - Incoterm)

VAT:

19 %

Buyers Premium:

16 %

Location:

Germany

Images:











SOKRATHERM® BHKW-Komplettmodul
BHKW-Compact CHP unit

BHKW-Typ CHP-type	GG 140 S 0 E	Spezifikation specification	WP 7L-70 B	Baujahr year of construction	2011
elektrische Nennleistung rated electric power	142 kW	thermische Nennleistung rated thermal power	216 kW	Energieeinsatz energy input	392 kW
Fertigungsnummer serial number	F110102	Aufstellhöhe altitude	<100 m üNN	max. Lufttemperatur max. air temperature	25 °C
Nendrehzahl rated speed	1500 1/min	Steuerspannung control voltage	24 V	Nennleistungsfaktor rated power factor	$\cos \varphi$ 0,8
Nennspannung rated voltage	400 V	max. Heizwasseraustritt max. heating water outlet			

Video:

Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33

Fax.: +49 2151 65 29 22

Email: info@asset-trade.de

Web.: <https://mail.asset-trade.de/en>

Generated on 16.02.2026

© Copyright 2026 - [Asset-Trade](#)

Page