

Image not found or type unknown



Ref. No.:  
1411-03211135

## Overview and Technical Data:

# MITUTOYO Crysta-Apex S7106 High-performance CMM

MITUTOYO

# Mitutoyo

Year of Build:  
Jan 2013

## Description:

### Used MITUTOYO Crysta-Apex S7106 CNC coordinate measuring machine

CNC Control U400

Technical data:

- Measuring range:
  - X-Axis: 700 mm (27.6")
  - Y-Axis: 1.000 mm (39.36")
  - Z-Axis: 600 mm (23.62")
- Resolution: 0.0001 mm (0.000004")
- Guide method: Air bearings on each axis
- Drive Speed:
  - Max. moving speed: 519 mm/s (20.4"/s) (3D)
  - Max. measuring speed: 8 mm/s
- Max. drive acceleration: 2,309 mm/s<sup>2</sup> (3D)
- Working Table Granit:
  - Size: 880 x 1720 mm
  - Gewindeinsätze: M8 x 1,25mm
- Workpiece
  - Max. Height: 800mm (31.49")
  - Max. Load: 1.000kg

Other Options:

- Inlk Temperature Correction unit

- J/S BOX M Type A
- SP25M Probe
- Renishaw PH6M
- inkl Safety rack MRS 400.

Software Information:

- MCOSMOS-2
- 

## **CRYSTA-Apex S Series**

**The Crysta-Apex S is a high accuracy, high Speed Moving Bridge Type Co-ordinate Measuring Machine utilising a Granite Base, which also provides the Y-Axis, guide way. A self-adjusting air bearing is used on each axis to provide stability during high-speed movement and measurement. The moving Bridge is constructed of low mass alloy, the “X” Beam and “Z” Spindle external surfaces being impregnated by an oxide coating process to form an extremely hard surface, which improves stability and also provides good wear resistance. Power drive is activated via a remote joystick unit for manual drive operation.**

The Crysta-Apex S is a high accuracy, high Speed Moving Bridge Type Co-ordinate Measuring Machine utilising a Granite Base, which also provides the Y-Axis, guide way. A self-adjusting air bearing is used on each axis to provide stability during high-speed movement and measurement. The moving Bridge is constructed of low mass alloy, the “X” Beam and “Z” Spindle external surfaces being impregnated by an oxide coating process to form an extremely hard surface, which improves stability and also provides good wear resistance. Power drive is activated via a remote joystick unit for manual drive operation.

The latest generation of CRYSTA-Apex coordinate measuring machines, the new CRYSTA-Apex S Series, is packed with the advanced technology needed to perform very accurate measurements at high speed. The new CRYSTA-Apex S-Series uses Mitutoyo's world-renowned scales and features high environmental resistance without the need for homing at startup. SMS capability enables status and service monitoring and is suitable for use in a smart factory environment.

As a future-proof investment, the CRYSTA-Apex S is capable of handling any future task thanks to its ability to easily change or add probe systems and software.

### **Key advantages:**

- Proven lightweight bridge design with highly rigid air bearings on each axis.
- High accuracy, high speed and high acceleration
- Temperature sensors to compensate machine and workpiece from 16° is 26°C and monitor ambient temperature.
- MITUTOYO linear scales offer high environmental resistance and save time during commissioning as no reference run is required
- Controller supports multi-sensor and SMS functionality (Smart Measuring system)

### **Technical Data:**

### **Technical Data:**

Control:

[CNC](#)

## **Dimensions and Weight:**

Height:  
2.730 mm  
Length:  
1.950 mm  
Width:  
1.470 mm  
Weight:  
1.951 kg

## **Buyer Information:**

Condition:  
[Very good condition](#)  
Available:  
[Sold](#)  
Sold as:  
[EXW \(Ex Works - Incoterm\)](#)  
VAT:  
[19 %](#)  
Location:  
Germany

## **Images:**





Mitutoyo


*CRYSTA*





















M rver\produktion\Maschinen\Messmaschine\CAT\_1000\BAKER\Fixture Heat\10592987\_6v.6\

Teilname	Erstellt	Zeit	Geändert
<b>Support Rib End</b>	<b>15.04.2021</b>	<b>14:30:39</b>	<b>15.04.2021</b>
Support Rib 113.0	15.04.2021	14:30:39	12.01.2023
np	15.04.2021	13:53:16	15.04.2021
New Part	08.03.2022	13:43:21	08.03.2022

OK













CRYSTA-APEX S

Mitutoyo  
COORDINATE  
MEASURING MACHINE

7106

MICROCORD

Hoffmann Group

Perschmann Calibration

Hoffmann Group

Hoffmann Group

Mitutoyo











Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33

Fax.: +49 2151 65 29 22

Email: [info@asset-trade.de](mailto:info@asset-trade.de)

Web.: <https://mail.asset-trade.de/en>

Ref. No.:

1411-03211135

**Overview and Technical Data:**

# MITUTOYO Crysta-Apex S7106 High-performance CMM

MITUTOYO

# Mitutoyo

Year of Build:  
Jan 2013

## Description:

**Used MITUTOYO Crysta-Apex S7106 CNC coordinate measuring machine**

CNC Control U400

## Technical data:

- Measuring range:
  - X-Axis: 700 mm (27.6")
  - Y-Axis: 1.000 mm (39.36")
  - Z-Axis: 600 mm (23.62")
- Resolution: 0.0001 mm (0.000004")
- Guide method: Air bearings on each axis
- Drive Speed:
  - Max. moving speed: 519 mm/s (20.4"/s) (3D)
  - Max. measuring speed: 8 mm/s
- Max. drive acceleration: 2,309 mm/s<sup>2</sup> (3D)
- Working Table Granit:
  - Size: 880 x 1720 mm
  - Gewindeinsätze: M8 x 1,25mm
- Workpiece
  - Max. Height: 800mm (31.49")
  - Max. Load: 1.000kg

## Other Options:

- Inlk Temperature Correction unit
- J/S BOX M Type A
- SP25M Probe
- Renishaw PH6M
- inkl Safety rack MRS 400.

## Software Information:

- MCOSMOS-2

---

## CRYSTA-Apex S Series

The Crysta-Apex S is a high accuracy, high Speed Moving Bridge Type Co-ordinate Measuring Machine utilising a Granite Base, which also provides the Y-Axis, guide way. A self-adjusting air bearing is used on each axis to provide stability during high-speed movement and measurement. The moving Bridge is constructed of low mass alloy, the “X” Beam and “Z” Spindle external surfaces being impregnated by an oxide coating process to form an extremely hard surface, which improves stability and also provides good wear resistance. Power drive is activated via a remote joystick unit for manual drive operation.

The Crysta-Apex S is a high accuracy, high Speed Moving Bridge Type Co-ordinate Measuring Machine utilising a Granite Base, which also provides the Y-Axis, guide way. A self-adjusting air bearing is used on each axis to provide stability during high-speed movement and measurement. The moving Bridge is constructed of low mass alloy, the “X” Beam and “Z” Spindle external surfaces being impregnated by an oxide coating process to form an extremely hard surface, which improves stability and also provides good wear resistance. Power drive is activated via a remote joystick unit for manual drive operation.

The latest generation of CRYSTA-Apex coordinate measuring machines, the new CRYSTA-Apex S Series, is packed with the advanced technology needed to perform very accurate measurements at high speed. The new CRYSTA-Apex S-Series uses Mitutoyo's world-renowned scales and features high environmental resistance without the need for homing at startup. SMS capability enables status and service monitoring and is suitable for use in a smart factory environment.

As a future-proof investment, the CRYSTA-Apex S is capable of handling any future task thanks to its ability to easily change or add probe systems and software.

### Key advantages:

- Proven lightweight bridge design with highly rigid air bearings on each axis.
- High accuracy, high speed and high acceleration
- Temperature sensors to compensate machine and workpiece from 16° is 26°C and monitor ambient temperature.
- MITUTOYO linear scales offer high environmental resistance and save time during commissioning as no reference run is required
- Controller supports multi-sensor and SMS functionality (Smart Measuring system)

### Technical Data:

### Technical Data:

Control:

[CNC](#)

### Dimensions and Weight:

Height:

2.730 mm

Length:

1.950 mm

Width:

1.470 mm

Weight:  
1.951 kg

## **Buyer Information:**

Condition:

[Very good condition](#)

Available:

[Sold](#)

Sold as:

[EXW \(Ex Works - Incoterm\)](#)

VAT:

[19 %](#)

Location:

Germany

## **Images:**





Mitutoyo

CRYSTA





7106

CO  
MEASUR

MICROCORD




POWER



Mikulov  
 Softwarové řešení  
 01805/102-343  
 Mikulov  
 Hardwarové řešení  
 01805/102-333
















M rver\produktion\Maschinen\Messmaschine\CAT\_1000\BAKER\Fixture Heat\10592987\_6v.6\


Teilname	Erstellt	Zeit	Geändert
<b>Support Rib End</b>	<b>15.04.2021</b>	<b>14:30:39</b>	<b>15.04.2021</b>
Support Rib 113.0	15.04.2021	14:30:39	12.01.2023
np	15.04.2021	13:53:16	15.04.2021
New Part	08.03.2022	13:43:21	08.03.2022

OK























Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33

Fax.: +49 2151 65 29 22

Email: [info@asset-trade.de](mailto:info@asset-trade.de)

Web.: <https://mail.asset-trade.de/en>

Generated on 03.06.2026

© Copyright 2026 - [Asset-Trade](#)

Page