

Image not found or type unknown



Ref. No.:

1452-12231400

Overview and Technical Data:

Used ENGEL ES 650/155 HL Victory for sale

[ENGEL](#)



Year of Build:

Jan 2001

Description:

Buy used ENGEL ES 650/155 HL Victory injection molding machine

Technical data:

- Clamping force: 1500 KN
- Screw diameter: 50 mm
- Max. Shot weight: 440 g
- Clear tie bar spacing: 750 x 750 (tie barless)
- Min. mold installation height: 300 mm
- Max. Mold opening stroke: 600 mm
- Centering ring diameter: 160 mm
- Number of core pulls: 1
- Cascade control: no
- Handling: yes

Handling Geiger LR 16 EC

- X axis: 500 mm
 - Y axis: 1200 mm
 - Z axis: 1900 mm
 - Interface: Euromap 67
 - Protective housing 2000 mm x 2000 mm with safety package
-

The tie-bar-less victory injection moulding machine is the ideal machine for a wide range of technical injection moulding applications and processes. The proven tie-bar-less technology ensures a particularly even clamping force distribution. For large moulds with low clamping force requirements, you only invest in the clamping force that is actually needed.

Technical Data:

Technical Data:

Control:

[CNC](#)

Machine Hours:

61432

Dimensions and Weight:

Height:

2.200 mm

Length:

5.600 mm

Width:

1.800 mm

Weight:

11.500 kg

Buyer Information:

Condition:

[Very good condition](#)

Available:

[Immediately](#)

Sold as:

EXW (Ex Works - Incoterm)

VAT:

19 %

Buyers Premium:

18 %

Location:

Germany

Images:







- 9. Quersch. und Schrägbohrn an der Flankenscheitel gesichert?
- 10. Spindelverschleiß an Öl- und Wasserleitungen?
- 11. Arbeitsschutz bei Öl- und Wasserleitungen, Granulat und anderen Verunreinigungen?
- 12. Bei Verschleiß/Schaden: Funktionsfähigkeit (z.B. Anzeigen) einrichten?
- 13. Leuchteffizienz/-verteilung funktionstüchtig?

M 19
 Engel
 E3 600/155 HS, Victory
 044417

SVS-V 2.11-DD184 V2K Tested IP: 132.168.288.188

TEMP ON

ESC F1 F2 F3 F4 F5 F6 F7 F8

7 8 9
 4 5 6
 1 2 3
 +/- 0

ENTER
 CLEAR

Navigation buttons (up, down, left, right, home, search, etc.)

Function buttons (e.g., alarm, stop, reset, etc.)

ENGEL

Buttons for: LÜFTVENTIL, START, PROGRAMMIERUNG, AUTOMATISCH, HAND, Überprüfungsstatus, WERKZEUGE L2/L4, SICHERHEITSTASTE, STEUERUNGSPANNE, NOT, ZYLINDER, NOT - AUS

Emergency stop button (red)













GEIGER HANDLING®
LR 16

GEIGER HANDLING
GmbH
Industriestraße 14
D-72173 Gengen
Tel: 07146 9710-0
Fax: 07146 9710-11
info@geiger-handling.de
www.geiger-handling.de



Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33

Fax.: +49 2151 65 29 22

Email: info@asset-trade.de

Web.: <https://mail.asset-trade.de/en>

Ref. No.:
1452-12231400

Overview and Technical Data:

Used ENGEL ES 650/155 HL Victory for sale

[ENGEL](#)



Year of Build:
Jan 2001

Description:

Buy used ENGEL ES 650/155 HL Victory injection molding machine

Technical data:

- Clamping force: 1500 KN
- Screw diameter: 50 mm
- Max. Shot weight: 440 g
- Clear tie bar spacing: 750 x 750 (tie barless)
- Min. mold installation height: 300 mm
- Max. Mold opening stroke: 600 mm
- Centering ring diameter: 160 mm
- Number of core pulls: 1

- Cascade control: no
- Handling: yes

Handling Geiger LR 16 EC

- X axis: 500 mm
 - Y axis: 1200 mm
 - Z axis: 1900 mm
 - Interface:Euromap 67
 - Protective housing 2000 mm x 2000 mm with safety package
-

The tie-bar-less victory injection moulding machine is the ideal machine for a wide range of technical injection moulding applications and processes. The proven tie-bar-less technology ensures a particularly even clamping force distribution. For large moulds with low clamping force requirements, you only invest in the clamping force that is actually needed.

Technical Data:

Technical Data:

Control:

[CNC](#)

Machine Hours:

61432

Dimensions and Weight:

Height:

2.200 mm

Length:

5.600 mm

Width:

1.800 mm

Weight:

11.500 kg

Buyer Information:

Condition:

[Very good condition](#)

Available:

[Immediately](#)

Sold as:

[EXW \(Ex Works - Incoterm\)](#)

VAT:

[19 %](#)

Buyers Premium:

[18 %](#)

Location:

Germany

Images:







- 9. Querschnitt und Schweißnaht an der Fließbohrbohrung geprüft?
- 10. Spritzschweißnaht an Öl- und Wasserbohrungen?
- 11. Aufwandszeit für die Montage, Demontage und die Wartung?
- 12. Bei der Montage/Schweißnaht funktionstüchtig (z.B. Anpressen) angeschlossen?
- 13. Leuchteffizienz / Wartungs funktionstüchtig?

M 19
 Engel
 E3 600/155 HS, Victory
 044417

SVS-V 2.11-DD184 V2K Tested IP: 132.168.288.188

TEMP ON

ESC F1 F2 F3 F4 F5 F6 F7 F8

7 8 9
 4 5 6
 1 2 3
 +/- 0

ENTER
 CLEAR

Navigation buttons (up, down, left, right, home, search, etc.)

Function buttons (e.g., power, reset, stop, start, etc.)

ENGEL

Navigation buttons (e.g., left, right, up, down, etc.)

LIFTVENTS

Buttons for LIFTVENTS

START PROGRAMMIERUNG AUTOMATISCH WARE

START (green button), PROGRAMMIERUNG (yellow button), AUTOMATISCH (yellow button), WARE (yellow button)

WONZELUNG 12VDC

SICHERHEITSTASTE STEUERUNG NOTER ZULASSUNG NOT - AUS

SICHERHEITSTASTE (yellow button), STEUERUNG (yellow button), NOTER (yellow button), ZULASSUNG (yellow button), NOT - AUS (red button)











GEIGER HANDLING®
LR 16®

GEIGER HANDLING®

GEIGER Handling GmbH & Co.

Industriestraße 19

D-72771 Heilbronn

Telefon: 07141 907220

Fax: 07141 907221

mailto:info@geiger-handling.de

www.geiger-handling.de



GEIGER HANDLING®
LR 16

GEIGER HANDLING
GmbH
Industriestraße 14
D-72173 Gengen
Tel: 07146 9710-0
Fax: 07146 9710-1
info@geiger-handling.de
www.geiger-handling.de



Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33

Fax.: +49 2151 65 29 22

Email: info@asset-trade.de

Web.: <https://mail.asset-trade.de/en>

Generated on 16.02.2026

© Copyright 2026 - [Asset-Trade](#)

Page